# LIGHTING LED BATTENS & TUBES







# **UNI SERIES**IP65 BATTEN SERIES

The Uni IP65 Batten Series is waterproof, IK10 impact resistant and designed as the ideal upgrade product to replace existing surface mounted or suspended fluorescent battens in outdoor locations.

The IP65 Batten includes switch controlled tri-colour temperature options, an adjustable built-in motion sensor and the option to add an emergency backup battery.

#### **FEATURES**

- Ideal for outside locations
- IP65 and IK10 rating
- Optional maintained emergency light
- Sensor with adjustable dim levels and hold times
- Tri-colour

### **SPECIFICATIONS**

POWER FACTOR	>0.9
CRI	>80
BEAM ANGLE	120
IP RATING	65
LIFETIME (L <sub>70</sub> )	>60,000hrs
WARRANTY	5 Years

#### **SENSOR SETTINGS**

DETECTION RANGE	5 or 10 metres
HOLD TIME	1m, 5m, 15mins or infinite
DAYLIGHT SENSOR	50Lux or disabled
STANDBY PERIOD	Os, <b>5m</b> , 30m or infinite
STANDBY LEVEL	<b>10</b> , 20, 30 or 50%

Highlighted values = sensor default settings

### LPM = LCP LOW POWER MODE

MODEL NUMBER	ССТ	DIMENSIONS	WATT	LCP	LPM	LUMENS	EFFICACY
IP65 TRI-COLOUR	1						
EP-UNI-T665-18	4/5/6000K	600mm	18	18.23		2313	127lm/W
EP-UNI-T1265-25	4/5/6000K	1200mm	25	23.82		3261	137lm/W
EP-UNI-T1265-35	4/5/6000K	1200mm	35	34.82		4689	135lm/W
IP65 TRI-COLOUR WITH SENSOR							
EP-UNI-TS665-18	4/5/6000K	600mm	18	17.4	1.7	2214	127lm/W
EP-UNI-TS1265-25	4/5/6000K	1200mm	25	24.94	2.5	3287	132lm/W
EP-UNI-TS1265-35	4/5/6000K	1200mm	35	35	3.5	4200	120lm/W







